

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014394-R1
DATE: 05/08/2019
CERTIFICATION PROGRAM: Structural
COMPANY: Eurocraft
CODE: 2409-1
REVISION DATE: 04/25/2022

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|-----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eurocraft Industries, Inc. 7905 Northwest 77th Avenue Medley, FL 33166 | Series "88MD Lift & Slide" Vinyl Sliding Glass Door Configuration: OXXO Glazing: IG- 1/4" Tempered Glass/3/16" Heat Strengthened Glass/0.090" Kuraray America SGP Interlayer/3/16" Heat Strengthened Glass or 1/4" Tempered Glass/3/16" Heat Strengthened Glass/0.090" Kuraray America PVB Interlayer/3/16" Heat Strengthened Glass or Monolithic- 1/4" Heat Strengthened Glass/0.090" Kuraray America SGP Interlayer/1/4" Heat Strengthened Glass or 1/4" Heat Strengthened Glass/0.090" Kuraray America PVB Interlayer/1/4" Heat Strengthened Glass Frame: W-5588mm(220") H-3048mm(120") DLO: W-1294mm(50.96") H-2834mm(111.58") |

| SPECIFICATION | PRODUCT RATING |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| TAS 201/202/203-94 | Design Pressure: ±5746 Pa (120 psf) Water Penetration Resistance Test Pressure: 862 Pa (18 psf) Large Missile Impact Rated |

Product Tested By: Blackwater Testing, Inc.
Report No: BT-EUR-18-001
Expiration Date: April 30, 2024

Administrator's Signature: _____


NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway
Hayes, VA 23072

Tel: (804) 684-5124

Email: nami@namiinc.com