

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015124.01-R1
DATE: 12/10/2020
CERTIFICATION PROGRAM: Structural
COMPANY: Plastpro
CODE: 1108-1
REVISION DATE: 03/14/2024

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Plastpro, Inc. 4747 Kister Court Ashtabula, OH 44004</p>	<p style="text-align: center;">Series “Plastpro Insert Glazing Series”</p> <p style="text-align: center;">Fiberglass 8/0 Inswing Door w/PVC Edge,</p> <p style="text-align: center;">Insert Glazing, and Adjustable Cap</p> <p style="text-align: center;">Configuration: XX Glazing: Insulated Glass (Tempered)</p> <p>Frame: W-1878mm(73.94") H-2488mm(97.94")</p> <p>Panel: W-908mm(35.75") H-2419mm(95.25")</p> <p>DLO: W-533mm(21") H-2007mm(79")</p>

SPECIFICATION	PRODUCT RATING
<p>AAMA/WDMA/CSA 101/I.S.2/A440-11 AAMA/WDMA/CSA 101/I.S.2/A440-08 A440S1-09</p>	<p style="text-align: center;">Class R-PG20 1878 x 2488 (74 x 98)-SHD</p> <p style="text-align: center;">Design Pressure: 960 Pa (20 psf)</p> <p style="text-align: center;">Positive Design Pressure: 1680 Pa (35 psf)</p> <p style="text-align: center;">Negative Design Pressure: 1680 Pa (35 psf)</p> <p style="text-align: center;">Water Penetration Resistance Test Pressure: 150 Pa (3.00 psf)</p> <p style="text-align: center;">Canadian Air Infiltration/Exfiltration Level: A3</p>

Product Tested By: National Certified Testing Laboratories
 Report No: NCTL-110-16786-2
 Expiration Date: **December 31, 2028**

Administrator’s Signature: _____

NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.
 4794 George Washington Memorial Highway
 Hayes, VA 23072
 Tel: (804) 684-5124
 Email: nami@namiinc.com