

# NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI013766.03-R2  
**DATE:** 06/28/2017  
**CERTIFICATION PROGRAM:** Structural  
**COMPANY:** Soft-Lite  
**CODE:** 2336-1  
**REVISION DATE:** 06/03/2024

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Soft-Lite Windows</b> <b>10250 Phillip Parkway</b> <b>Streetsboro, OH 44241</b>	<b>Series "Barcelona"</b> <b>Vinyl Horizontal Sliding Window</b> <b>(TSL 30I)</b>  Configuration: XOX Glazing: IG-1/8" Annealed Glass/Laminate-0.106" Annealed Glass/0.090" Saflex PVB Interlayer/0.106" Annealed Glass or 1/8" Tempered Glass/Laminate-0.106" Annealed Glass/0.090" Saflex PVB Interlayer/0.106" Annealed Glass Frame: W-2819mm(111") H-1600mm(63") Sash: W-933mm(36.75") H-1480mm(58.25") DLO: W-832mm(32.75") H-1378mm(54.25")

SPECIFICATION	PRODUCT RATING
<b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b> <b>ASTM E1886-05</b> <b>ASTM E1996-09</b>	<b>Class R-PG55 2819 x 1600 (111 x 63)-HS</b> <b>Design Pressure: ±2633 Pa (55 psf)</b> <b>Positive Design Pressure: 2633 Pa (55 psf)</b> <b>Negative Design Pressure: 2873 Pa (60 psf)</b> Water Penetration resistance Test Pressure: 395 Pa (8.25 psf) <b>Wind Zone 3 - Missile Level D</b>

Product Tested By: Testing Evaluation Laboratories, Inc.  
Report No: TEL 03001871/TEL 03001872  
Expiration Date: June 30, 2027

Administrator's Signature: \_\_\_\_\_ 

**NATIONAL ACCREDITATION AND  
MANAGEMENT INSTITUTE, INC.**  
4794 George Washington Memorial Highway  
Hayes, VA 23072  
Tel: (804) 684-5124/Email: [nami@namiinc.com](mailto:nami@namiinc.com)

NOPC-03/30/2023