## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014426-R5

DATE: 05/23/2019

**CERTIFICATION PROGRAM:** Fire

**COMPANY:** Builders First

**CODE:** <u>2479-1</u>

REVISION DATE: <u>09/07/2023</u> EXPIRATION DATE: <u>05/31/2025</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Builders First Source</b>	20 Minute Neutral Pressure Fire Door
8809 Paul Starr Road	Assemblies w/o Hose Stream
Pensacola, FL 32514	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999)	20 Minute-Neutral Pressure
UL 10B (2009)	Without Hose Stream
<b>UBC Standard 7-2 (1997)</b>	

## **TEST REPORT**

Intertek Test Report No: 3073067, 3043898, 307008-1, 100108677COQ-001, 3059877, J20012862-23, 3025659, 3192291COQ-005, 3048495, 3108034COQ-003, Warnock-Hershey Test Report No: WHI-495-1685, WHI-495-1197, WHI-495-0897

Administrator's Signature:



## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com