NOTICE OF PRODUCT CERTIFICATION



| CERTIFICA | ATION NO: |
|------------------------|-----------|
| | DATE |
| CERTIFICATION P | ROGRAM |
| С | OMPANY |
| | CODE |
| | |

| NI015157.03 |
|--------------|
| 02/10/2021 |
| Structural |
| Sunrise Win. |
| 2483-1 |

To verify that the "Notice of Product Certification" is valid, please visit <u>www.NAMICertification.com</u> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION | | |
|--------------------------|--|------------------|------------------|
| Sunrise Windows, LTD | Series "Coastal Performance" | | |
| 200 Enterprise Drive | Vinyl Sliding Glass Door | | |
| Temperance, MI 48182 | (Impact) | | |
| | Configuration: XO Glazing: IG - 5/32" Tempered Glass/5/32" Annealed Glass/0.090" SentryGlas PVB Interlayer/5/32" Annealed Glass | | |
| | Frame: | W-2438mm(96") | H-2438mm(96") |
| | Panel: | W-1235mm(48.63") | H-2330mm(91.75") |
| | DLO: | W-1057mm(41.63") | H-2172mm(85.5") |

| SPECIFICATION | PRODUCT RATING |
|---|--|
| AAMA/WDMA/CSA 101/I.S.2/A440-17 ASTM E1886-13a ASTM E1996-14a | Class LC-PG50 2438 x 2438 (96 x 96)-SD Design Pressure: 2400 Pa (50 psf) Water Penetration Resistance Test Pressure: 360 Pa (7.50 psf) |
| AS1101 E1770-14a | Wind Zone 3 - Missile Level D |

Product Tested By: Report No: Expiration Date: Testing Evaluation Laboratories TEL 15503186/TEL 15503191 November 30, 2024

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 Fax: (804) 684-5122