## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015187

**COMPANY:** 

**DATE:** 03/18/2021

CERTIFICATION PROGRAM: Fire

BMC Millwork

CODE: 1665-1

**EXPIRATION DATE:** 03/31/2025

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
BMC Millwork Corporation	20-Minute Composite Wood Fire Door
399 Northpoint Parkway	(Particleboard, Agristrand, Agri-Fiber or 22 pcf LDF Core)
Acworth, GA 30102	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 4'0" x 10'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2012/2017) UL 10C (2009/2015/2016) UL 10B (2009/2015) UBC Standard 7-2 (1994/1997) CAN/ULC S104 (2010/2015)	20 Minute-Neutral/Positive Pressure With Hose Stream Category B - Additional Edge-Sealing System Required Category A - No additional Edge-Sealing System Required

TEST REPORT	
Intertek Test Report No: 3125646COQ-004	

Administrator's Signature:	
----------------------------	--

110

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122