NOTICE OF PRODUCT CERTIFICATION



To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

PRODUCT DESCRIPTION
20 Minute Positive Pressure
Flush or Molded Interior Side-Hinged
Door w/Wheatboard Core
Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION

NFPA 252 (1999) UL 10(b) (1997/2009) CAN4-S104 (1985) UBC Standard 7-2 (1994/1997) UL 10(c) (2009) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3137714COQ-008

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124/ Fax: (804) 684-5122