NOTICE OF PRODUCT CERTIFICATION

| 1065 ACCREDITED A | CERTIFICATION NO: | NI015217-R3 |
|---------------------------|-------------------------------|-----------------------|
| Stand and a contract Roog | DATE: | 04/16/2021 |
| | CERTIFICATION PROGRAM: | Fire |
| | COMPANY: | Builders First |
| ATTAC THE | CODE: | <u>2621-1</u> |
| CEATIFIED PRODUCT | REVISION DATE: | 09/07/2023 |
| COPIC- | EXPIRATION DATE: | 04/30/2024 |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION | |
|------------------------------------------|------------------------------------------------------------------------------------------|--|
| Builders First Source Corporation | Plastpro 90 Minute Positive Pressure | |
| 7700 Caldwell Drive | Fire Door Assemblies w/Hose Stream | |
| Harrisburg, NC 28075 | Manufacturer Specific Fire Doors for Single Swing Installation in 90 Minute Locations | |
| | 1/2" Minimum Latch Throw Single Swing Only | |
| | Maximum Size: 4'0" x 8'0" | |
| | Minimum Thickness: 1-3/4" | |

SPECIFICATION

NFPA 252 (1999)/UL 10C (2001)/ UL 10B (1997) UBC 7-2 (1994) CAN4 S104 (1985) **PRODUCT RATING**

90 Minute-Positive Pressure With Hose Stream Category B - Additional Edge Sealing System Required

TEST REPORT

Intertek Test Report No: 3058118-02, 3058118-01

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com