

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015246-R1
DATE: 04/28/2021
CERTIFICATION PROGRAM: Fire
COMPANY: SGM Door
CODE: 2743-1
REVISION DATE: 05/07/2025
EXPIRATION DATE: 04/30/2028

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|---|--|
| SGM Doors and Trim, LLC 11500 Main Street, Suite 118 Houston, TX 77025 | Crest Doors 20 Minute Positive Pressure Particleboard Core/Wood Veneer Side-Hinged Door Assembly Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations 1/2" Minimum Latch Throw Single & Double Swing Only Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Minimum Thickness: 1-3/4" |

| SPECIFICATION | PRODUCT RATING |
|---|---|
| UBC-7-2-97 UL 10C (1998)(2009) NFPA 252 (1995)(2008) | 20 Minute-Positive Pressure w/o Hose Stream Category A Door-No Additional Edge Seal Required Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing) |

| TEST REPORT |
|---|
| Warnock Hershey Test Report No: WHI-495-1367 |

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

nami@namiinc.com

NOPC-03/30/2023

