## NOTICE OF PRODUCT CERTIFICATION



<b>CERTIFICATION NO:</b>	NIUI
DATE:	<u>04/28</u>
<b>CERTIFICATION PROGRAM:</b>	<u>Fire</u>
<b>COMPANY:</b>	SGM
CODE:	<u>2743</u>
<b>EXPIRATION DATE:</b>	<u>04/3</u>

NI015251	
04/28/2021	
Fire	
SGM Door	
2743-1	
04/30/2025	

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
SGM Doors and Trim, LLC	20-Minute Aurora Composite Fire Door
14625 Minetta Street, Bldg B	
Houston, TX 77035	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

## **SPECIFICATION**

NFPA 252 (1999/2008/2012) UL 10C (2001/2009) UL 10B (1997/2009) UBC Standard 7-2 (1994/1997) CAN/ULC S104 (2010) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B - Additional Edge-Sealing System Required

## **TEST REPORT**

Intertek Test Report No: 100854038COQ-006

Shi

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122