NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015258

DATE: 04/28/2021

CERTIFICATION PROGRAM: Fire

COMPANY: SGM Door

CODE: 2743-1

EXPIRATION DATE: 04/30/2025

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
SGM Doors and Trim, LLC	20 Minute Positive & Neutral Pressure
14625 Minetta Street, Bldg B	Flush or Molded Interior Side-Hinged
Houston, TX 77035	Door w/Particleboard Core
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999)	20 Minute-Neutral/Positive Pressure
UL 10(b) (2009)	With Hose Stream
ASTM E2074 (2000)	Category B Door-Additional Edge Seal
CAN4-S104(ULC S104)	Required
UBC Standard 7-2 (1994/1997)	For Use in Category C Frame
UL 10(c) (1998)	(or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT	
Intertek Test Report No: 3137713COQ-007	

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124/ Fax: (804) 684-5122