NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015262

DATE: 04/28/2021

CERTIFICATION PROGRAM: Fire

COMPANY: SGM Door

CODE: <u>2743-1</u>

EXPIRATION DATE: 04/30/2025

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
SGM Doors and Trim, LLC	Plastpro's 60 Minute Positive Pressure
14625 Minetta Street, Bldg B	Fire Door Assemblies w/Hose Stream
Houston, TX 77035	Manufacturer Specific Fire Doors for Single Swing Installation in 60 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 6'8"
	Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2008)(2012)/UL 10C (2009)/	60 Minute-Positive Pressure
CAN4 S104 (1985)/	With Hose Stream
CAN/ULC S104 (2010)	Category B - Additional Edge Sealing
	System Required

TEST REPORT	_
Intertek Test Report No: 3175675MID-004, 3196317MID-001	

Administrator's Signature:	DAY	

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122