NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:	NIU.
DATE:	<u>04/2</u>
CERTIFICATION PROGRAM:	Fire
COMPANY:	SGN
CODE:	<u>2743</u>
EXPIRATION DATE:	<u>04/3</u>

NI015263	
04/28/2021	
Fire	
SGM Door	
2743-1	
04/30/2025	

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
SGM Doors and Trim, LLC	Plastpro 90 Minute Positive Pressure	
14625 Minetta Street, Bldg B	Fire Door Assemblies w/Hose Stream	
Houston, TX 77035	Manufacturer Specific Fire Doors for Single Swing Installation in 90 Minute Locations	
	1/2" Minimum Latch Throw Single Swing Only	
	Maximum Size: 4'0" x 8'0"	
	Minimum Thickness: 1-3/4"	

SPECIFICATION

NFPA 252 (1999)/UL 10C (2001)/ UL 10B (1997) UBC 7-2 (1994) CAN4 S104 (1985) **PRODUCT RATING**

90 Minute-Positive Pressure With Hose Stream Category B - Additional Edge Sealing System Required

TEST REPORT

Intertek Test Report No: 3058118-02, 3058118-01

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 Fax: (804) 684-5122