NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015266-R3

DATE: 04/29/2021

CERTIFICATION PROGRAM: Fire

COMPANY: Builders First

CODE: <u>2621-1</u>

REVISION DATE: <u>09/07/2023</u> **EXPIRATION DATE:** <u>04/30/2025</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
Builders First Source Corporation	20 Minute Positive Pressure	
7700 Caldwell Drive	Flush or Molded Interior Side-Hinged	
Harrisburg, NC 28075	Door w/Wheatboard Core	
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single Swing Only	
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"	

SPECIFICATION	PRODUCT RATING	
NFPA 252 (1999) UL 10(b) (1997/2009)	20 Minute-Positive Pressure With Hose Stream	
CAN4-S104 (1985) UBC Standard 7-2 (1994/1997) UL 10(c) (2009)	Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)	

TEST	REP	ORT
------	-----	-----

Intertek Test Report No: 3137714COQ-008

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com