## **NOTICE OF PRODUCT CERTIFICATION**



<b>CERTIFICATION NO:</b>
DATE:
<b>CERTIFICATION PROGRAM:</b>
<b>COMPANY:</b>
CODE:
<b>EXPIRATION DATE:</b>

NI015294	
06/10/2021	
Fire	
Doorscapes	
1834-1	
06/30/2025	

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Doorscapes, Inc.	20 Minute Neutral Pressure Fire Door
11833 Cutten Road, Suite 200	Assemblies w/o Hose Stream
Houston, TX 77066	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 8'0" x 8'0" Minimum Thickness: 1-3/4"

**SPECIFICATION** 

NFPA 252 (1999) UL 10B (2009) UBC Standard 7-2 (1997) **PRODUCT RATING** 

20 Minute-Neutral Pressure Without Hose Stream

## **TEST REPORT**

Intertek Test Report No: 3073067, 3043898, 307008-1, 100108677COQ-001, 3059877, J20012862-23, 3025659, 3192291COQ-005, 3048495, 3108034COQ-003, Warnock-Hershey Test Report No: WHI-495-1685, WHI-495-1197, WHI-495-0897

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

> Tel: (804) 684-5124 Fax: (804) 684-5122