## **NOTICE OF PRODUCT CERTIFICATION**



To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Doorscapes, Inc.	20-Minute Aurora Composite Fire Door
11833 Cutten Road, Suite 200	
Houston, TX 77066	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

## **SPECIFICATION**

NFPA 252 (1999/2008/2012) UL 10C (2001/2009) UL 10B (1997/2009) UBC Standard 7-2 (1994/1997) CAN/ULC S104 (2010) 20 Minute-Positive Pressure With Hose Stream

**PRODUCT RATING** 

Category B - Additional Edge-Sealing System Required

## **TEST REPORT**

Intertek Test Report No: 100854038COQ-006

Sh

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122