## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO: NI015298** 

**DATE:** 06/10/2021

**CERTIFICATION PROGRAM:** Fire

**COMPANY:** <u>Doorscapes</u>

CODE: <u>1834-1</u>

**EXPIRATION DATE:** 06/30/2025

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Doorscapes, Inc.	20-Minute Foam-Filled
11833 Cutten Road, Suite 200	Steel Fire Door
Houston, TX 77066	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 6'8" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2012/2017)	20 Minute-Neutral Pressure
UL 10B (2009/2015)	Without Hose Stream

## **TEST REPORT**

Intertek Test Report No: 100108677COQ-001, G100108677, G100237215, G100211525, G100754937, G102772178

Administrator's Signature:



## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5124