NOTICE OF PRODUCT CERTIFICATION



To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

PRODUCT DESCRIPTION
20-Minute
Single Swing Wood Door Frame
Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Maximum Size: 3'1-3/8" x 7'2" Minimum Thickness: 3-3/4"

SPECIFICATION

NFPA 252 (1995/2008) UL 10(b) (1997/2009) CAN/ULC S104 (1985/2010) 20 Minute-Neutral Pressure With Hose Stream Category C- Proprietary Frame

PRODUCT RATING

TEST REPORT

Warnock Hershey Test Report No: WHI-3010, WHI-495-1094, WHI-495-1525

Sh.

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124Fax: (804) 684-5122