NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015306

DATE: 06/16/2021

CERTIFICATION PROGRAM: 1

PROGRAM: <u>Fire</u>
COMPANY: <u>Doorscapes</u>

CODE: 1834-1

EXPIRATION DATE: 06/30/2025

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Doorscapes, Inc.	PlastPro 20 Minute Positive Pressure
11833 Cutten Road, Suite 200	Fire Door Assemblies w/o Hose Stream
Houston, TX 77066	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) UL 10C (2009)	20 Minute-Positive Pressure Without Hose Stream
UBC Standard 7-2 (1997)	Category B Door-Additional Edge Seal Required (unless specified in individual manufacturer's listing)
	For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3182549MID-005, 100644112MID-002, 100644112MID-004, 3178456MID-003, 3182549MID-005b, 100359215MID-010b

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

Fax: (804) 684-5122