## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI015307

**DATE:** 06/16/2021

CERTIFICATION PROGRAM: Fire

COMPANY: Doorscapes

**CODE:** 1834-1

**EXPIRATION DATE:** <u>06/30/2025</u>

To verify that the "Notice of Product Certification" is valid, please visit <a href="www.NAMICertification.com">www.NAMICertification.com</a> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Doorscapes, Inc.	PlastPro 60 Minute Positive Pressure
11833 Cutten Road, Suite 200	Fire Door Assemblies w/Hose Stream
Houston, TX 77066	Manufacturer Specific Fire Doors for Single Swing Installation in 60 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 6'8"
	Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2008)(2012)/UL 10C (2009)/	60 Minute-Positive Pressure
CAN4 S104 (1985)/	With Hose Stream
CAN/ULC S104 (2010)	Category B - Additional Edge Sealing
	System Required

TEST REPORT	
Intertek Test Report No: 3175675MID-004, 3196317MID-001	

	Shiel .	
Administrator's Signature:		

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124/ Fax: (804) 684-5122