

NAMI NOTICE OF PRODUCT LINE CERTIFICATION



Certification No.: NI011316-R2 Page 1
Date: 07/25/2016
Certification Program: Structural
Company: Guy C. Lee
Code: 610-1
Revision Date: 04/13/2023
Expiration Date: 03/31/2025

The "Notice of Product Line Certification" is valid only when Administrator's Seal is applied to the upper left hand portion of this form and a certification label is applied to the product. This certification seal represents product conformity to the applicable specification and that all certification criteria have been satisfied.

The products and systems listed below are approved for listing in the Directory of Certified Products at www.NAMICertification.com. Please review, and advise NAMI immediately if data, as shown requires corrections.

Company: **Guy C. Lee Millwork**
1251 South Pollock Street
Selma, NC 27576

Product Line: **Jeld-Wen's Contours/Energy Saver Glazed Wood Edge Steel Entry Doors w/Glazed Sidelites**

Test Report: **NCTL-110-11987-1, NCTL-110-11988-1 & SJW2009-200**

Section 1: General Description of the Products and Systems under this Certification

- 1.1 Frame:** The frame jambs consist of wood with all corners coped and butted. The head/jamb corners were fastened with three (4) 16 ga 7/16" crown x 2" long staples per corner. The threshold was attached to the side jambs with three (3) 16 ga 7/16" x 2" long wire staples and (2) #8 2-1/2" long screws at each end.
- 1.2 Door Panel/Sidelite Construction:** Each door panel was constructed from two (2) face sheets of 24 gauge (0.021" minimum) galvanized steel and an internal expanded polystyrene foam core.
- 1.3 Sidelite Glazing:** The overall insulated glass unit was comprised of two (2) 1/8" sheets of clear tempered glass.

National Accreditation & Management Institute, Inc.
4794 George Washington Memorial Highway, Hayes, VA 23072
Tel(804) 684-5124 nami@namiinc.com

Section 2: Registered Suppliers

- 2.1 Door Lites: ODL**
- 2.2 Astragal: Endura Ultimate Hurricane**
- 2.3 Sills Endura ZOBL4566/Endura FOB4566A**

Section 3: Additional Supportive Test or Acceptance Data provided with Certification Documentation included:

- 3.1 Surface Burning Characteristics of Building Materials, ASTM E84-08, Dylite Expandable Polystyrene, Intertek Report Number 3113726SAT-001 Rev.1.**
- 3.2 Standard Test Methods for Tension Testing of Metallic Materials, ASTM E8-08, Steel Door Skins, ETC Laboratories, Report No. ETC-08-056-21686.0.**
- 3.3 Product Evaluation Report #2948 prepared by Alexis Spyrou, P.E., Texas Professional Engineer # 102957, Dated 07/14/2014.**

See additional Pages of Certification for Certified Product Line Matrix(s) and Installation Details. If you have any questions regarding this certification, please contact NAMI at (804) 684-5124.

NOTICE OF PRODUCT CERTIFICATION



Company: Guy C. Lee Millwork
1251 South Pollock Street
Selma, NC 27576

Certification No.: NI013316-R2 Page 3
Certification Date: 07/25/2016
Revision Date: 04/13/2023
Expiration Date: 03/31/2025

Product: Jeld-Wen's Contour/Energy Saver Glazed Wood Edge Steel Door w/ or w/o Glazed Side-Lites (w/Wood Frame unless noted)

Specification: ASTM E283-04/E330-02/E331-00

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| Configuration | Inswing or Outswing | Glazed or Opaque | Maximum Size | Design Pressure Pos/Neg | Missile Impact Rated | Test Report Number Drawing Number & Comments |
|-------------------------|---------------------|------------------|--------------|-------------------------|----------------------|--|
| X Single | I/S or O/S | Glazed | 3'2" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| X Single | I/S or O/S | Glazed | 3'2" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OX/XO Single w/Sidelite | I/S or O/S | Glazed | 6'3" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OX/XO Single w/Sidelite | I/S or O/S | Glazed | 6'3" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OXO Single w/Sidelite | I/S or O/S | Glazed | 9'4" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OXO Single w/Sidelite | I/S or O/S | Glazed | 9'4" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____

NOTICE OF PRODUCT CERTIFICATION



Company: Guy C. Lee Millwork
1251 South Pollock Street
Selma, NC 27576

Certification No.: NI013316-R2 Page 4
Certification Date: 07/25/2016
Revision Date: 04/13/2023
Expiration Date: 03/31/2025

Product: Jeld-Wen's Contour/Energy Saver Glazed Wood Edge Steel Door w/ or w/o Glazed Side-Lites (w/Wood Frame unless noted)

Specification: ASTM E283-04/E330-02/E331-00

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| Configuration | Inswing or Outswing | Glazed or Opaque | Maximum Size | Design Pressure Pos/Neg | Missile Impact Rated | Test Report Number Drawing Number & Comments |
|---------------------------|---------------------|------------------|---------------|-------------------------|----------------------|--|
| XX Double | I/S or O/S | Glazed | 6'2" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| XX Double | I/S or O/S | Glazed | 6'2" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |
| XXO/OXX Double w/Sidelite | I/S or O/S | Glazed | 9'4" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| XXO/OXX Double w/Sidelite | I/S or O/S | Glazed | 9'4" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OXXO Double w/Sidelites | I/S or O/S | Glazed | 12'5" x 6'10" | +55/-55 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: A008730/A008731/AO11294 |
| OXXO Double w/Sidelites | I/S or O/S | Glazed | 12'5" x 6'10" | +66/-66 | No | NCTL-110-11987-1/110-11988-1/SJW2009-200/PER2948/W-1694 Max Panel Size: 3'0" x 6'7"/Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: A008730/A008731/AO11294 |

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____