

NOTICE OF PRODUCT CERTIFICATION



Company: DW Distribution, Inc.
1220 Centre Park Boulevard
De Soto, TX 75115

Certification No.: NI015416.06
Certification Date: 08/30/2021
Expiration Date: 08/31/2025

Product: Fiberglass Opaque Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E330-02/ASTM E1886-05/13a/ASTM E1996-09/14a

Impact: Missile Level D Non-Impact Sidelites: Insulating Glass (Tempered)

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 8'0"	+70/-70	0.0 psf	Yes	NCTL-210-3835-1/W-1972 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0210-17
X Single	O/S	Opaque	3'0" x 8'0"	+70/-70	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁴	Yes	NCTL-210-3835-1/W-1843/W-1972 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0210-17
XX Double	I/S	Opaque	6'0" x 8'0"	+50/-50	0 psf	Yes	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1972 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
XX Double	O/S	Opaque	6'0" x 8'0"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁴	Yes	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1843/W-1972 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 8'0"	+50/-50	0 psf	Door-Yes Sidelite-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
XO/OX Single w/Sidelite	O/S	Opaque Door Glazed Sidelite	6'0" x 8'0"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁴	Door-Yes Sidelite-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1843/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelite	9'0" x 8'0"	+50/-50	0 psf	Door-Yes Sidelites-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	9'0" x 8'0"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁴	Door-Yes Sidelites-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1843/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
OXXO Double w/Sidelites	I/S	Opaque Door Glazed Sidelite	12'4" x 8'0"	+50/-50	0 psf	Door-Yes Sidelites-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17
OXXO Double w/Sidelites	O/S	Opaque Door Glazed Sidelite	12'4" x 8'0"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁴	Door-Yes Sidelites-No	NCTL-210-3849-1/ATLNC 0306.01-17/0308.01-17/W-1843/W-1972 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0188-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Worldwide Pro T4 Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____