NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:	NI
DATE:	01/
CERTIFICATION PROGRAM:	Fi
COMPANY:	Tr
CODE:	<u>28</u>
EXPIRATION DATE:	<u>01</u> /

NI015489 01/10/2022 Fire Truitt & White 2807-1 01/31/2026

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Truitt & White Lumber Company, Inc.	20 Minute Positive Pressure
642 Hearst Avenue	Molded Simulated Panel Side-Hinged
Berkeley, CA 94710	Side-Hinged Door Assembly
	Manufacturer Specific Fire Doors for Single Swing or Standard Pairs Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing or Standard Pairs Only
	Single Swing Maximum Size: 3'0" x 8'0" Standard Pairs Maximum Size: 6'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION

NFPA 252 (1999) UL 10(b) (2009) CAN4-S104 (1985)(2010) UL 10(c) (2009) PRODUCT RATING

20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance

with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3192291COQ-005, 100211525COQ-001, 100553244COQ-002, 100581395MID-001, 101432263COQ

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com