## NOTICE OF PRODUCT CERTIFICATION



<b>CERTIFICATION NO:</b>	<b>NI0</b> 1
DATE:	<u>01/1</u>
<b>CERTIFICATION PROGRAM:</b>	Fire
<b>COMPANY:</b>	<u>Trui</u>
CODE:	<u>2807</u>
<b>EXPIRATION DATE:</b>	01/3

NI015491
01/10/2022
Fire
Truitt & White
2807-1
01/31/2026

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Truitt & White Lumber Company, Inc.	20-Minute Conmore Routed
642 Hearst Avenue	Particleboard Core Fire Door
Berkeley, CA 94710	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 7'0" Minimum Thickness: 1-3/4"

## **SPECIFICATION**

NFPA 252 (2008) UL 10C (2001) CAN/ULC S104 (1985) 20 Minute-Positive Pressure With Hose Stream Category B - Additional Edge-Sealing System Required

**PRODUCT RATING** 

## **TEST REPORT**

Intertek Test Report No: 3176461MID-003, 3169881, G100027980, G100418906, G103408699 NAMI Waiver of Retest: W-1998

Shi

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com