NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:	NI
DATE:	<u>01</u> /
CERTIFICATION PROGRAM:	Fii
COMPANY:	Tr
CODE:	<u>28</u>
EXPIRATION DATE:	<u>01</u> /

NI015495		
01/10/2022		
Fire		
Truitt & White		
2807-1		
01/31/2026		

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Truitt & White Lumber Company, Inc.	"Madison/Monroe/Craftsman/Birkdale"
642 Hearst Avenue	Molded Panel Composite Fire Doors
Berkeley, CA 94710	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" (Must refer to listing for size/rating limitations) Minimum Thickness: 1-11/16"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2012/2017) UL 10C (2009/2015/2016) UL 10B (2009/2015)	20 Minute-Positive or Neutral Pressure With Hose Stream Category B - Additional Edge-Sealing
CAN/ULC S104 (2015)	System Required

TEST REPORT

Intertek Test Report No: 2192291COQ-005, 101070204COQ-001B Intertek EEV No: 100921055COQ-001, 103667744MID-001, 104106427MID-001, 1029627719MID-001 NAMI Waiver of Retest: W-1998

Sh

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com