# **NOTICE OF PRODUCT CERTIFICATION**

ACCRED/A		
1065 ACCRED DO	<b>CERTIFICATION NO:</b>	<u>NI015510-R1</u>
Sy round of the B	DATE:	01/25/2022
	<b>CERTIFICATION PROGRAM:</b>	Fire
	<b>COMPANY:</b>	<b>Boise Cascade</b>
ARA TIL	CODE:	2820-1
CERTIS OPPOSIT	<b>REVISION DATE:</b>	03/05/2024
THED PROV	<b>EXPIRATION DATE:</b>	<u>01/31/2026</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

<b>COMPANY NAME AND ADDRESS</b>	
Boise Cascade	Therma Tru 20 Minute Fiberglass Door
1020 West 3265 Street	w/Proprietary Foam Core
Salt Lake City, UT 84119	(Simulated, Flush or Shaker Panel Type)
	Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations
	Single Door Maximum Size: 36" x 96" Shaker Single Door Maximum Size: 36" x 80"
	Minimum Thickness: 1-3/4"

#### **SPECIFICATION**

UL 10C (2016) NFPA 252 (2012)

#### **PRODUCT RATING**

20 Minute-without Hose Stream Positive Pressure Category B- Additional Edge Sealing Required

### **TEST REPORT**

Intertek Test Report No: 103875182MID-007

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com