NOTICE OF PRODUCT CERTIFICATION

CERTIFICATION NO:	<u>NI015511-R1</u>
DATE:	01/25/2022
CERTIFICATION PROGRAM:	Fire
COMPANY:	Boise Cascade
CODE:	<u>2820-1</u>
REVISION DATE:	03/05/2024
EXPIRATION DATE:	01/31/2026
	DATE: CERTIFICATION PROGRAM: COMPANY: CODE: REVISION DATE:

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Boise Cascade	20 Minute Positive Pressure
1020 West 3265 Street	Flush or Molded Interior Side-Hinged
Salt Lake City, UT 84119	Door w/Wheatboard Core
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION

NFPA 252 (1999) UL 10(b) (1997/2009) CAN4-S104 (1985) UBC Standard 7-2 (1994/1997) UL 10(c) (2009) 20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

PRODUCT RATING

TEST REPORT

Intertek Test Report No: 3137714COQ-008

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023