

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015539
DATE: 02/28/2022
CERTIFICATION PROGRAM: Fire
COMPANY: Caldera
CODE: 2830-1
EXPIRATION DATE: 02/28/2026

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Caldera Industries, LLC 2980 South Wise Way Boise, ID 83716	20 Minute Positive Pressure Molded Simulated Panel Side-Hinged Side-Hinged Door Assembly Manufacturer Specific Fire Doors for Single Swing or Standard Pairs Installation in 20 Minute Locations 1/2" Minimum Latch Throw Single Swing or Standard Pairs Only Single Swing Maximum Size: 3'0" x 8'0" Standard Pairs Maximum Size: 6'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) UL 10(b) (2009) CAN4-S104 (1985)(2010) UL 10(c) (2009)	20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT
Intertek Test Report No: 3192291COQ-005, 100211525COQ-001, 100553244COQ-002, 100581395MID-001, 101432263COQ

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway
Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com