## **NOTICE OF PRODUCT CERTIFICATION**



To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Caldera Industries, LLC	"ABS 20-Minute"
2980 South Wise Way	<b>Routed Particleboard Fire Door</b>
Boise, ID 83716	Manufacturer Specific Fire Doors for Single Swing Installation in 20-Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	20-Minute Single Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATIONPFNFPA 252 (2012)20 MiUL 10C (2009)WCategory I

**PRODUCT RATING** 

20 Minute-Positive Pressure Without Hose Stream Category B - Additional Edge-Sealing System Required

## **TEST REPORT**

Intertek Test Report No: 3107376COQ-004, 3169105, 3043898, 102245905, 104375792

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com