## **NOTICE OF PRODUCT CERTIFICATION**



To verify that the "Notice of Product Certification" is valid, please visit <u>www.NAMICertification.com</u> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Bjornstad Construction Company</b>	Endura 20 Minute Category C
1240 Texan Trail, Suite 102	<b>Proprietary Wood Door Frames</b>
Grapevine, TX 76051	
	Manufacture Specific Fire Door Frames for Double Swing Installation in 20 Minute Locations
	Single Door Maximum Size: 8'0" x 9'0"
	Minimum Jamb Depth: 3.5"

SPECIFICATION	<b>PRODUCT RATING</b>
NFPA 252 (2012)	20 Minute-With Hose Stream Positive Pressure
UL 10b (1997) UL 10c (2009)	Category C- Proprietary Frame
CAN/ULC S104 (2010) UBC Standard 7-2 (1994)	

## **TEST REPORT**

Intertek Test Report No(s): 101305789COQ-002, 101664134COQ-002 Intertek Engineering Evaluation No(s): 102343380MID-001

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com