

# NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014011-R2  
DATE: 04/04/2018  
CERTIFICATION PROGRAM: Fire  
COMPANY: Gator Build Sup  
CODE: 2152-1  
REVISION DATE: 03/17/2026  
EXPIRATION DATE: 04/30/2029

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Gator Building Supply, Inc.</b> <b>9555 North US 1</b> <b>Sebastian, FL 32958</b>	<b>20 Minute Positive Pressure</b> <b>Flush or Molded Interior Side-Hinged</b> <b>Door w/Wheatboard Core</b>  Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations  1/2" Minimum Latch Throw Single Swing Only  <b>Maximum Size: 3'0" x 8'0"</b> <b>Minimum Thickness: 1-3/4"</b>

SPECIFICATION	PRODUCT RATING
<b>NFPA 252 (1999)</b> <b>UL 10(b) (1997/2009)</b> <b>CAN4-S104 (1985)</b> <b>UBC Standard 7-2 (1994/1997)</b> <b>UL 10(c) (2009)</b>	<b>20 Minute-Positive Pressure</b> <b>With Hose Stream</b> <b>Category B Door-Additional Edge Seal</b> <b>Required</b> <b>For Use in Category C Frame</b> (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT
<b>Intertek Test Report No: 3137714COQ-008</b>

Administrator's Signature: 

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

[nami@namiinc.com](mailto:nami@namiinc.com)

NOPC-03/30/2023