

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:	<u>NI015611.02</u>
DATE:	<u>08/09/2022</u>
CERTIFICATION PROGRAM:	<u>Structural</u>
COMPANY:	<u>Sunset Windows</u>
CODE:	<u>2348-1</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Sunset Windows and Doors, LLC 910 Warehouse Road, Unit 110104 Orlando, FL 32803</p>	<p style="text-align: center;">Series "V-750"</p> <p style="text-align: center;">Vinyl Horizontal Sliding Window</p> <p style="text-align: center;">(w/1.125" Sill Riser)</p> <p style="text-align: center;">Configuration: OX Glazing: Mono-3/16" Heat Strengthened Glass/0.090 Trosifol or SGP PVB by Kuraray/3/16" Heat Strengthened Glass IG-Ext. 5/32" Tempered Glass/ Int. 5/32" Heat Strengthened Glass/0.090 PVB or SGP by Kuraray/5/32" Heat Strengthened Glass</p> <p>Frame: W-1880mm(74") H-1829mm(72") Sash: W-965mm(38") H-1778mm(70") DLO: W-762mm(30") H-1588mm(62.50")</p>

SPECIFICATION	PRODUCT RATING
<p>AAMA/WDMA/CSA 101/I.S.2/A440-17 AAMA/WDMA/CSA 101/I.S.2/A440-11 ASTM E1886-12/13a ASTM E1996-12a/14a</p>	<p>Class CW-PG60 1880 x 1829 (74 x 72)-HS Design Pressure: ±2880 Pa (±60 psf) Water Penetration Resistance Level: 431 Pa (9.00 psf) Wind Zone 4 - Missile Level D Large Missile Impact Rated</p>

Product Tested By: National Certified Testing Laboratories

Report No: NCTL-210-4227-04A

Expiration Date: **February 28, 2026**

Administrator's Signature: _____

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124/Email: nami@namiinc.com