## **NOTICE OF PRODUCT CERTIFICATION**

ACCREDITED	<b>CERTIFICATION NO:</b>	NI015668-R2
4 STAL ACCREDITAD	DATE:	08/16/2022
So and a start and a start	<b>CERTIFICATION PROGRAM:</b>	Fire
	<b>COMPANY:</b>	<b>Builders First</b>
Carton Contraction	CODE:	<u>1665-1</u>
CERT TINST	<b>REVISION DATE:</b>	<u>09/07/2023</u>
TIFIED PROUS	<b>EXPIRATION DATE:</b>	<u>08/31/2026</u>
W 100 V		

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Builders First Source	<b>Composite Technology Internationsl</b>
399 Northpoint Parkway	20-Minute Fire-Rated (Without Hose)
Acworth, GA 30102	Single or Double Swing Wood Door Frame
	Manufacture Specific Fire Door Frames for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw
	Single or Double Swing Only
	Single Maximum Size: 4'0" x 8'0"
	Double Maximum Size: 8'0" x 8'0"
	Minimum Thickness: 4-1/2"

## **SPECIFICATION**

NFPA 252 (2008/2017) UL 10(c) (2009)

## **PRODUCT RATING**

20 Minute-Positive Pressure Without Hose Stream

## **TEST REPORT**

Intertek Test Report No: 100535906MID-004, 100535906MID-005 Intertek Engineering Evaluation: 100535906MID-006

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com