

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Masonite International Corporation  
1955 Powis Road  
West Chicago, IL 60185

**Certification No.:** NI013717.23-R1  
**Certification Date:** 10/12/2022  
**Expiration Date:** 05/31/2027  
**Revision Date:** 12/06/2023

**Product:** Fiberglass Opaque Inswing or Outswing Door w/ and w/o Impact Rated Sidelites w/Endura Trilennium or Panolock Multi-Point Hardware (w/Wood Frame or Worldwide Composite Frame<sup>4</sup> unless noted)

**Specification:** TAS 202-94/ASTM E330-02/14/M-14/ASTM E1886-05/13a/ASTM E1996-09/14a

**Impact:** Missile Level D Impact Glazing: IG-1/8" Tempered Glass/1/8" Heat-Strengthened Glass/0.090 Saflex PVB Interlayer/1/8" Heat-Strengthened Glass

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| Configuration           | Inswing or Outswing | Glazed or Opaque            | Maximum Size | Structural Design Pressure | Water Test Pressure  | Missile Impact Rated   | Test Report Number Drawing Number & Comments  |
|-------------------------|---------------------|-----------------------------|--------------|----------------------------|--|------------------------|---|
| X Single                | I/S                 | Opaque                      | 3'0" x 6'8"  | +50/-50                    | 0.0 psf  | Yes                    | NCTL-210-3835-1/W-1812/W-1916/W-1972/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0197-19  |
| X Single                | O/S                 | Opaque                      | 3'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup><br>7.5 psf <sup>6</sup> | Yes                    | NCTL-210-3835-1/W-1812/W-1813/W-1843/W-1860/W-1916/W-1972/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-MA-FL0197-19   |
| XX Double               | I/S                 | Opaque                      | 6'0" x 6'8"  | +50/-50                    | 0 psf  | Yes                    | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1916/W-1972/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0197-19   |
| XX Double               | O/S                 | Opaque                      | 6'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>                        | Yes                    | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843/W-1916/W-1972/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0197-19   |
| XO/OX Single w/Sidelite | I/S                 | Opaque Door Glazed Sidelite | 6'0" x 6'8"  | +50/-50                    | 0 psf  | Door-Yes Sidelite-Yes  | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22               |
| XO/OX Single w/Sidelite | O/S                 | Opaque Door Glazed Sidelite | 6'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>                         | Door-Yes Sidelite-Yes  | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1813/W-1843/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22 |
| OXO Single w/Sidelites  | I/S                 | Opaque Door Glazed Sidelite | 9'0" x 6'8"  | +50/-50                    | 0 psf  | Door-Yes Sidelites-yes | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22               |
| OXO Single w/Sidelites  | O/S                 | Opaque Door Glazed Sidelite | 9'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>                         | Door-Yes Sidelites-Yes | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1813/W-1843/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22 |
| OXXO Double w/Sidelites | I/S                 | Opaque Door Glazed Sidelite | 12'4" x 6'8" | +50/-50                    | 0 psf  | Door-Yes Sidelites-Yes | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22               |
| OXXO Double w/Sidelites | O/S                 | Opaque Door Glazed Sidelite | 12'4" x 6'8" | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>                        | Door-Yes Sidelites-Yes | ATLNC 0831.01-16/ATLNC 0901.02-16/ATLNC 1222.01-15/W-1813/W-1843/W-1916/W-1972/W-2048/W-2106/W-2107<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0257-22 |

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold 6-Denotes HP Outswing Threshold

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072**

**Tel: (804) 684-5124/nami@namiinc.com**

**NAMI AUTHORIZED SIGNATURE:** \_\_\_\_\_