

# Notice of Product Certification

CERTIFICATION NO.: 2864-002  
 INITIAL CERTIFICATION DATE: November 1, 2022  
 REVISION DATE: N/A  
 REPORT NUMBER: VWD22107594-bR  
 SPECIFICATION: CSA A440.2-19

COMPANY: Rhino Windows, Inc.  
 CODE: 2864-1  
 EXPIRATION DATE: July 26, 2027  
 PRODUCT SIMULATED BY: WSP  
 AIR LEAKAGE REPORT NO.: L19-925-5637aw

PRODUCT/SERIES NAME: 150 Awning

OPERATOR TYPE: PRAW

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2864-002-0001-01	272-arg95-SDCI 3-3 (7/8" OT), ss	0.042(#2)	1.48	0.27	0.47	0.3	23
2864-002-0001-02	272-arg95-SDCI 3-3 (7/8" OT), ss, Grids<1"	0.042(#2)	1.48	0.25	0.42	0.3	21
2864-002-0002-01	272-arg95-SDCI 3-3 (7/8" OT), ss, Foam	0.042(#2)	1.45	0.27	0.47	0.3	23
2864-002-0002-02	272-arg95-SDCI 3-3 (7/8" OT), ss, Foam, Grids<1"	0.042(#2)	1.45	0.25	0.42	0.3	22
2864-002-0003-01	SDCI-arg95-PTLUX 3-3 (7/8" OT), ss	0.082(#3)	1.54	0.49	0.52	0.3	34
2864-002-0003-02	SDCI-arg95-PTLUX 3-3 (7/8" OT), ss, Grids<1"	0.082(#3)	1.54	0.45	0.47	0.3	32
2864-002-0004-01	272-arg95-SDCI-air-SDCI 3-3-3 (1 3/8" OT), ss	0.042(#2)	1.21	0.25	0.43	0.3	27
2864-002-0004-02	272-arg95-SDCI-air-SDCI 3-3-3 (1 3/8" OT), ss, Grids<1"	0.042(#2)	1.21	0.23	0.39	0.3	26
2864-002-0005-01	272-arg95-272-arg95-SDCI 3-3-3 (1 3/8" OT), ss	0.042(#2, #4)	0.96	0.21	0.37	0.3	31
2864-002-0005-02	272-arg95-272-arg95-SDCI 3-3-3 (1 3/8" OT), ss, Grids<1"	0.042(#2, #4)	0.96	0.20	0.34	0.3	30
2864-002-0006-01	SDCI-air-SDCI-arg95-PTLUX 3-3-3 (1 3/8" OT), ss	0.082(#5)	1.22	0.46	0.48	0.3	39
2864-002-0006-02	SDCI-air-SDCI-arg95-PTLUX 3-3-3 (1 3/8" OT), ss, Grids<1"	0.082(#5)	1.22	0.41	0.43	0.3	36
2864-002-0007-01	SDCI-arg95-PTLUX-arg95-PTLUX 3-3-3 (1 3/8" OT), ss	0.082(#3, #5)	1.00	0.43	0.46	0.3	42
2864-002-0007-02	SDCI-arg95-PTLUX-arg95-PTLUX 3-3-3 (1 3/8" OT), ss, Grids<1"	0.082(#3, #5)	1.00	0.39	0.41	0.3	40
2864-002-0008-01	VCI-arg95-PTLUX 4-3 (7/8" OT), ss	0.082(#3)	1.53	0.45	0.51	0.3	32
2864-002-0008-02	VCI-arg95-PTLUX 4-3 (7/8" OT), ss, Grids<1"	0.082(#3)	1.53	0.41	0.46	0.3	30
2864-002-0009-01	VCI-arg95-PTLUX 4-4 (7/8" OT), ss	0.081(#3)	1.53	0.45	0.50	0.3	32
2864-002-0009-02	VCI-arg95-PTLUX 4-4 (7/8" OT), ss, Grids<1"	0.081(#3)	1.53	0.41	0.45	0.3	30
2864-002-0010-01	VCI-arg95-PTLUX 6-3 (1 1/8" OT), ss	0.082(#3)	1.55	0.43	0.50	0.3	30
2864-002-0010-02	VCI-arg95-PTLUX 6-3 (1 1/8" OT), ss, Grids<1"	0.082(#3)	1.55	0.39	0.45	0.3	28
2864-002-0011-01	VCI-arg95-PTLUX 6-4 (1 3/8" OT), ss	0.081(#3)	1.56	0.43	0.50	0.3	30
2864-002-0011-02	VCI-arg95-PTLUX 6-4 (1 3/8" OT), ss, Grids<1"	0.081(#3)	1.56	0.39	0.45	0.3	28
2864-002-0012-01	VCI-arg95-PTLUX 6-3 (1 3/8" OT), ss	0.082(#3)	1.56	0.43	0.50	0.3	30
2864-002-0012-02	VCI-arg95-PTLUX 6-3 (1 3/8" OT), ss, Grids<1"	0.082(#3)	1.56	0.39	0.45	0.3	28
2864-002-0013-01	CLLam-arg95-PTLUX 6-4 (1 3/8" OT), ss	0.081(#3)	1.54	0.43	0.50	0.3	31

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2864-002-0013-02	CLLam-arg95-PTLUX 6-4 (1 3/8" OT), ss, Grids<1"	0.081(#3)	1.54	0.39	0.45	0.3	28
2864-002-0014-01	CLLam-arg95-PTLUX 6-6 (1 3/8" OT), ss	0.081(#3)	1.54	0.43	0.49	0.3	31
2864-002-0014-02	CLLam-arg95-PTLUX 6-6 (1 3/8" OT), ss, Grids<1"	0.081(#3)	1.54	0.39	0.44	0.3	28
2864-002-0015-01	CLLam-arg95-PTLUXLam 6-6 (1 3/8" OT), ss	0.087(#3)	1.54	0.42	0.50	0.3	30
2864-002-0015-02	CLLam-arg95-PTLUXLam 6-6 (1 3/8" OT), ss, Grids<1"	0.087(#3)	1.54	0.38	0.45	0.3	28
2864-002-0016-01	CLLam-arg95-PTLUX 9-6 (1 3/8" OT), ss	0.081(#3)	1.54	0.42	0.49	0.3	30
2864-002-0016-02	CLLam-arg95-PTLUX 9-6 (1 3/8" OT), ss, Grids<1"	0.081(#3)	1.54	0.38	0.44	0.3	28

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

National Accreditation & Management Institute, Inc.  
 4794 George Washington Memorial Hwy.  
 Hayes, VA 23072  
 Tel.: (804) 684-5124  
 nami@namiinc.com  
 namicertification.com