

Notice of Product Certification

CERTIFICATION NO.: 1228-012

INITIAL CERTIFICATION DATE: February 2, 2023

REVISION DATE: N/A

REPORT NUMBER: SPL22001-6-C_HSOX-P

SPECIFICATION: CSA A440.2-19

COMPANY: Portes et Fenetres Varin Inc.

CODE: 1228-1

EXPIRATION DATE: August 31, 2027

PRODUCT SIMULATED BY: Veridis Solutions Inc.

AIR LEAKAGE REPORT NO.: AI-04110-E1 Rev.1

PRODUCT/SERIES NAME: Coulissant Simple PVC 9620-9820 **OPERATOR TYPE:** HSOX

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-012-0001-01	GL,3mm_7/8_GCl-arg95-8071, im	0.082(#3)	1.62	0.52	0.59	0.4	34
1228-012-0002-01	GL,3mm_7/8_GCl-arg95-8071, im, Grids<1"	0.082(#3)	1.62	0.47	0.52	0.4	31
1228-012-0003-01	GL,3mm_7/8_GCl-arg95-8071, im, Grids>1"	0.082(#3)	1.62	0.41	0.46	0.4	27
1228-012-0004-01	GL,3mm_7/8_STCl-arg95-8071, im	0.082(#3)	1.62	0.54	0.59	0.4	35
1228-012-0005-01	GL,3mm_7/8_STCl-arg95-8071, im, Grids<1"	0.082(#3)	1.62	0.49	0.53	0.4	32
1228-012-0006-01	GL,3mm_7/8_STCl-arg95-8071, im, Grids>1"	0.082(#3)	1.62	0.43	0.46	0.4	29
1228-012-0007-01	GL,3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.58	0.52	0.59	0.4	35
1228-012-0008-01	GL,3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.47	0.52	0.4	32
1228-012-0009-01	GL,3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.41	0.46	0.4	28
1228-012-0010-01	GL,3mm_7/8_STCl-arg95-8071, sp	0.082(#3)	1.58	0.54	0.59	0.4	36
1228-012-0011-01	GL,3mm_7/8_STCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.49	0.53	0.4	33
1228-012-0012-01	GL,3mm_7/8_STCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.43	0.46	0.4	29
1228-012-0013-01	BF_3mm_7/8_GCl-arg95-8071, im	0.082(#3)	1.62	0.52	0.59	0.4	34
1228-012-0014-01	BF_3mm_7/8_GCl-arg95-8071, im, Grids<1"	0.082(#3)	1.62	0.47	0.52	0.4	31
1228-012-0015-01	BF_3mm_7/8_GCl-arg95-8071, im, Grids>1"	0.082(#3)	1.62	0.41	0.46	0.4	27
1228-012-0016-01	BF_3mm_7/8_STCl-arg95-8071, im	0.082(#3)	1.62	0.54	0.59	0.4	35
1228-012-0017-01	BF_3mm_7/8_STCl-arg95-8071, im, Grids<1"	0.082(#3)	1.62	0.49	0.53	0.4	32
1228-012-0018-01	BF_3mm_7/8_STCl-arg95-8071, im, Grids>1"	0.082(#3)	1.62	0.43	0.46	0.4	29
1228-012-0019-01	BF_3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.58	0.52	0.59	0.4	35
1228-012-0020-01	BF_3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.47	0.52	0.4	32

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-012-0021-01	BF_3mm_7/8_GCI-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.41	0.46	0.4	28
1228-012-0022-01	BF_3mm_7/8_STCI-arg95-8071, sp	0.082(#3)	1.58	0.54	0.59	0.4	36
1228-012-0023-01	BF_3mm_7/8_STCI-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.49	0.53	0.4	33
1228-012-0024-01	BF_3mm_7/8_STCI-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.43	0.46	0.4	29
1228-012-0025-01	GL_3mm_7/8_PCI-arg97-PTLX, ss	0.082(#3)	1.56	0.54	0.58	0.4	36
1228-012-0026-01	GL_3mm_7/8_PCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.56	0.48	0.52	0.4	33
1228-012-0027-01	GL_3mm_7/8_PCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.56	0.43	0.46	0.4	30
1228-012-0028-01	GL_3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.56	0.56	0.58	0.4	37
1228-012-0029-01	GL_3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.56	0.50	0.52	0.4	34
1228-012-0030-01	GL_3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.56	0.44	0.46	0.4	30
1228-012-0031-01	GL_3mm_7/8_PCI-arg97-PTLX, ms	0.082(#3)	1.61	0.54	0.58	0.4	35
1228-012-0032-01	GL_3mm_7/8_PCI-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.61	0.49	0.52	0.4	32
1228-012-0033-01	GL_3mm_7/8_PCI-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.61	0.43	0.46	0.4	29
1228-012-0034-01	BF_3mm_7/8_PCI-arg97-PTLX, ss	0.082(#3)	1.55	0.54	0.58	0.4	36
1228-012-0035-01	BF_3mm_7/8_PCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.55	0.48	0.52	0.4	33
1228-012-0036-01	BF_3mm_7/8_PCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.55	0.43	0.46	0.4	30
1228-012-0037-01	BF_3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.55	0.56	0.58	0.4	38
1228-012-0038-01	BF_3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.55	0.50	0.52	0.4	34
1228-012-0039-01	BF_3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.55	0.44	0.46	0.4	31
1228-012-0040-01	BF_3mm_7/8_PCI-arg97-PTLX, ms	0.082(#3)	1.61	0.54	0.58	0.4	35
1228-012-0041-01	BF_3mm_7/8_PCI-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.61	0.49	0.52	0.4	32
1228-012-0042-01	BF_3mm_7/8_PCI-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.61	0.43	0.46	0.4	29

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Administrator's Signature:



National Accreditation & Management Institute, Inc.
4794 George Washington Memorial Hwy.
Hayes, VA 23072
Tel.: (804) 684-5124
nami@namiinc.com
namicertification.com

