

Notice of Product Certification

CERTIFICATION NO.: 1228-013
INITIAL CERTIFICATION DATE: February 2, 2023
REVISION DATE: N/A
REPORT NUMBER: SPL22001-6-C_VSSH-H
SPECIFICATION: CSA A440.2-19

COMPANY: Portes et Fenetres Varin Inc.
CODE: 1228-1
EXPIRATION DATE: August 30, 2027
PRODUCT SIMULATED BY: Veridis Solutions Inc.
AIR LEAKAGE REPORT NO.: AI-04137-A1 Rev.1

PRODUCT/SERIES NAME: Guillotine Simple Hybride - 9020D **OPERATOR TYPE:** VSSH

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-013-0001-01	GL, 3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.66	0.52	0.58	0.5	33
1228-013-0002-01	GL, 3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.66	0.47	0.52	0.5	30
1228-013-0003-01	GL, 3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.66	0.41	0.46	0.5	26
1228-013-0004-01	GL, 3mm_7/8_STCl-arg95-8071, ms	0.082(#3)	1.66	0.54	0.59	0.5	34
1228-013-0005-01	GL, 3mm_7/8_STCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.66	0.49	0.53	0.5	31
1228-013-0006-01	GL, 3mm_7/8_STCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.66	0.43	0.46	0.5	27
1228-013-0007-01	GL, 3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.63	0.52	0.58	0.5	33
1228-013-0008-01	GL, 3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.63	0.47	0.52	0.5	30
1228-013-0009-01	GL, 3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.63	0.41	0.46	0.5	27
1228-013-0010-01	GL, 3mm_7/8_STCl-arg95-8071, sp	0.082(#3)	1.63	0.54	0.59	0.5	35
1228-013-0011-01	GL, 3mm_7/8_STCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.63	0.49	0.53	0.5	32
1228-013-0012-01	GL, 3mm_7/8_STCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.63	0.43	0.46	0.5	28
1228-013-0013-01	BF, 3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.64	0.52	0.58	0.5	33
1228-013-0014-01	BF, 3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.64	0.47	0.52	0.5	30
1228-013-0015-01	BF, 3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.64	0.41	0.46	0.5	27
1228-013-0016-01	BF, 3mm_7/8_STCl-arg95-8071, ms	0.082(#3)	1.64	0.54	0.59	0.5	34
1228-013-0017-01	BF, 3mm_7/8_STCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.64	0.49	0.53	0.5	31
1228-013-0018-01	BF, 3mm_7/8_STCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.64	0.43	0.46	0.5	28
1228-013-0019-01	BF, 3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.61	0.52	0.58	0.5	34
1228-013-0020-01	BF, 3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.61	0.47	0.52	0.5	31

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-013-0021-01	BF, 3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.61	0.41	0.46	0.5	27
1228-013-0022-01	BF, 3mm_7/8_STCl-arg95-8071, sp	0.082(#3)	1.61	0.54	0.59	0.5	35
1228-013-0023-01	BF, 3mm_7/8_STCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.61	0.49	0.53	0.5	32
1228-013-0024-01	BF, 3mm_7/8_STCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.61	0.43	0.46	0.5	29
1228-013-0025-01	GL, 3mm_7/8_PCl-arg97-PTLX, ss	0.082(#3)	1.61	0.54	0.58	0.5	35
1228-013-0026-01	GL, 3mm_7/8_PCl-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.61	0.48	0.52	0.5	31
1228-013-0027-01	GL, 3mm_7/8_PCl-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.61	0.43	0.45	0.5	29
1228-013-0028-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.61	0.56	0.58	0.5	36
1228-013-0029-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.61	0.50	0.52	0.5	33
1228-013-0030-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.61	0.44	0.46	0.5	29
1228-013-0031-01	GL, 3mm_7/8_PCl-arg97-PTLX, ms	0.082(#3)	1.65	0.54	0.58	0.5	34
1228-013-0032-01	GL, 3mm_7/8_PCl-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.65	0.48	0.52	0.5	31
1228-013-0033-01	GL, 3mm_7/8_PCl-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.65	0.43	0.45	0.5	28
1228-013-0034-01	BF, 3mm_7/8_PCl-arg97-PTLX, ss	0.082(#3)	1.59	0.54	0.58	0.5	35
1228-013-0035-01	BF, 3mm_7/8_PCl-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.59	0.48	0.52	0.5	32
1228-013-0036-01	BF, 3mm_7/8_PCl-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.59	0.43	0.45	0.5	29
1228-013-0037-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.59	0.56	0.58	0.5	37
1228-013-0038-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.59	0.50	0.52	0.5	33
1228-013-0039-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.59	0.44	0.46	0.5	30
1228-013-0040-01	BF, 3mm_7/8_PCl-arg97-PTLX, ms	0.082(#3)	1.63	0.54	0.58	0.5	35
1228-013-0041-01	BF, 3mm_7/8_PCl-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.63	0.48	0.52	0.5	31
1228-013-0042-01	BF, 3mm_7/8_PCl-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.63	0.43	0.45	0.5	28

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com