

Notice of Product Certification

CERTIFICATION NO.: 1228-015

COMPANY: Portes et Fenetres Varin Inc.

INITIAL CERTIFICATION DATE: February 2, 2023

CODE: 1228-1

REVISION DATE: N/A

EXPIRATION DATE: August 30, 2027

REPORT NUMBER: SPL22001-6-C_VSDH-H

PRODUCT SIMULATED BY: Veridis Solutions Inc.

SPECIFICATION: CSA A440.2-19

AIR LEAKAGE REPORT NO.: AI-04137-C1 Rev.1

PRODUCT/SERIES NAME: Guillotine Double Hybride - 9040D OPERATOR TYPE: VSDH

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-015-0001-01	GL, 3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.68	0.50	0.56	0.5	31
1228-015-0002-01	GL, 3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.68	0.45	0.50	0.5	28
1228-015-0003-01	GL, 3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.68	0.40	0.44	0.5	25
1228-015-0004-01	GL, 3mm_7/8_STCl-arg95-8071, ms	0.082(#3)	1.68	0.52	0.57	0.5	32
1228-015-0005-01	GL, 3mm_7/8_STCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.68	0.47	0.50	0.5	29
1228-015-0006-01	GL, 3mm_7/8_STCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.68	0.41	0.44	0.5	26
1228-015-0007-01	GL, 3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.64	0.50	0.56	0.5	32
1228-015-0008-01	GL, 3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.64	0.45	0.50	0.5	29
1228-015-0009-01	GL, 3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.64	0.40	0.44	0.5	26
1228-015-0010-01	GL, 3mm_7/8_STCl-arg95-8071, sp	0.082(#3)	1.64	0.52	0.57	0.5	33
1228-015-0011-01	GL, 3mm_7/8_STCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.64	0.47	0.50	0.5	30
1228-015-0012-01	GL, 3mm_7/8_STCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.64	0.41	0.44	0.5	27
1228-015-0013-01	BF, 3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.68	0.50	0.56	0.5	31
1228-015-0014-01	BF, 3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.68	0.45	0.50	0.5	28
1228-015-0015-01	BF, 3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.68	0.40	0.44	0.5	25
1228-015-0016-01	BF, 3mm_7/8_STCl-arg95-8071, ms	0.082(#3)	1.68	0.52	0.57	0.5	32
1228-015-0017-01	BF, 3mm_7/8_STCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.68	0.47	0.50	0.5	29
1228-015-0018-01	BF, 3mm_7/8_STCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.68	0.41	0.44	0.5	26
1228-015-0019-01	BF, 3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.64	0.50	0.56	0.5	32
1228-015-0020-01	BF, 3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.64	0.45	0.50	0.5	29

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1228-015-0021-01	BF, 3mm_7/8_GCI-arg95-8071, sp, Grids>1"	0.082(#3)	1.64	0.40	0.44	0.5	26
1228-015-0022-01	BF, 3mm_7/8_STCI-arg95-8071, sp	0.082(#3)	1.64	0.52	0.57	0.5	33
1228-015-0023-01	BF, 3mm_7/8_STCI-arg95-8071, sp, Grids<1"	0.082(#3)	1.64	0.47	0.50	0.5	30
1228-015-0024-01	BF, 3mm_7/8_STCI-arg95-8071, sp, Grids>1"	0.082(#3)	1.64	0.41	0.44	0.5	27
1228-015-0025-01	GL, 3mm_7/8_PCI-arg97-PTLX, ss	0.082(#3)	1.62	0.52	0.56	0.5	34
1228-015-0026-01	GL, 3mm_7/8_PCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.62	0.47	0.50	0.5	31
1228-015-0027-01	GL, 3mm_7/8_PCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.62	0.41	0.44	0.5	27
1228-015-0028-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.62	0.54	0.56	0.5	35
1228-015-0029-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.62	0.48	0.50	0.5	31
1228-015-0030-01	GL, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.62	0.42	0.44	0.5	28
1228-015-0031-01	GL, 3mm_7/8_PCI-arg97-PTLX, ms	0.082(#3)	1.68	0.52	0.56	0.5	32
1228-015-0032-01	GL, 3mm_7/8_PCI-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.68	0.47	0.50	0.5	29
1228-015-0033-01	GL, 3mm_7/8_PCI-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.68	0.41	0.44	0.5	26
1228-015-0034-01	BF, 3mm_7/8_PCI-arg97-PTLX, ss	0.082(#3)	1.62	0.52	0.56	0.5	34
1228-015-0035-01	BF, 3mm_7/8_PCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.62	0.47	0.50	0.5	31
1228-015-0036-01	BF, 3mm_7/8_PCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.62	0.41	0.44	0.5	27
1228-015-0037-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss	0.082(#3)	1.62	0.54	0.56	0.5	35
1228-015-0038-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids<1"	0.082(#3)	1.62	0.48	0.50	0.5	31
1228-015-0039-01	BF, 3mm_7/8_SDCI-arg97-PTLX, ss, Grids>1"	0.082(#3)	1.62	0.42	0.44	0.5	28
1228-015-0040-01	BF, 3mm_7/8_PCI-arg97-PTLX, ms	0.082(#3)	1.67	0.52	0.56	0.5	32
1228-015-0041-01	BF, 3mm_7/8_PCI-arg97-PTLX, ms, Grids<1"	0.082(#3)	1.67	0.47	0.50	0.5	30
1228-015-0042-01	BF, 3mm_7/8_PCI-arg97-PTLX, ms, Grids>1"	0.082(#3)	1.67	0.41	0.44	0.5	26

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com