NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015731-R1

DATE: 02/13/2023

CERTIFICATION PROGRAM: <u>Fire</u>

COMPANY: Kempsville

CODE: <u>2587-1</u>

REVISION DATE: <u>12/12/2023</u> **EXPIRATION DATE:** <u>02/28/2027</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Kempsville Building Materials Corp.	FyreWerks FC-20
3300 Business Center Drive	20 Minute Positive Pressure
Chesapeake, VA 23323	Side-Hinged Door
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single & Double Swing Only
	Single Maximum Size: 4'0" x 8'0" Double Maximum Size: 7'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UL 10(b) (2009) CAN4-S104 (2015) UL 10(c) (2009/2015) NFPA 252 (2012)	20 Minute-Positive Pressure w/Hose Stream Category A Door-No Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3061569, 3084820, 3121025, 3144298, 3159384, 3181657COQ-006, 10015449MID-001, 102627269MID-001, 103096847MID-001

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com