

Notice of Product Certification

CERTIFICATION NO.: 2901-008
 INITIAL CERTIFICATION DATE: March 7, 2023
 REVISION DATE: N/A
 REPORT NUMBER: AJR22110670-e
 SPECIFICATION: CSA A440.2-19

COMPANY: AJR Window Technologies
 CODE: 2901-1
 EXPIRATION DATE: January 18, 2028
 PRODUCT SIMULATED BY: WSP
 AIR LEAKAGE REPORT NO.: L14-905-3805b

PRODUCT/SERIES NAME: Single Slider OPERATOR TYPE: HSOX

| Product Number | Manufacturer Product Code | Emissivity (Surface #) | U-Factor (Metric) | SHGC(w) | Visible Transmittance (VT) | Air Leakage Average (L75) | Energy Rating |
|------------------|---------------------------------|------------------------|-------------------|---------|----------------------------|---------------------------|---------------|
| 2901-008-0001-01 | CCI-arg97-180, ss | 0.068(#3) | 1.62 | 0.54 | 0.62 | 0.5 | 35 |
| 2901-008-0001-02 | CCI-arg97-180, ss, Grids<1" | 0.068(#3) | 1.62 | 0.48 | 0.55 | 0.5 | 31 |
| 2901-008-0002-01 | GCI-arg97-8071, ss | 0.082(#3) | 1.64 | 0.56 | 0.62 | 0.5 | 35 |
| 2901-008-0002-02 | GCI-arg97-8071, ss, Grids<1" | 0.082(#3) | 1.64 | 0.50 | 0.56 | 0.5 | 32 |
| 2901-008-0003-01 | 180-arg97-i89, ss | 0.068(#2) 0.149(#4) | 1.38 | 0.49 | 0.60 | 0.5 | 37 |
| 2901-008-0003-02 | 180-arg97-i89, ss, Grids<1" | 0.068(#2) 0.149(#4) | 1.38 | 0.44 | 0.54 | 0.5 | 34 |
| 2901-008-0004-01 | CCI-arg97-CCI-arg97-180, ss | 0.068(#5) | 1.57 | 0.48 | 0.56 | 0.5 | 32 |
| 2901-008-0005-01 | GCI-arg97-GCI-arg97-8071, ss | 0.082(#5) | 1.58 | 0.50 | 0.57 | 0.5 | 33 |
| 2901-008-0006-01 | 180-arg97-CCI-arg97-180, ss | 0.068(#2, #5) | 1.35 | 0.44 | 0.54 | 0.5 | 35 |
| 2901-008-0007-01 | 8071-arg97-GCI-arg97-8071, ss | 0.082(#2, #5) | 1.37 | 0.46 | 0.56 | 0.5 | 36 |
| 2901-008-0008-01 | SPCI-arg90-SG400-arg90-VCI, iu | 0.113(#3) | 1.63 | 0.51 | 0.56 | 0.5 | 33 |
| 2901-008-0009-01 | SPCI-arg90-SPCI-arg90-SG400, iu | 0.113(#5) | 1.62 | 0.53 | 0.57 | 0.5 | 34 |
| 2901-008-0010-01 | VCI-arg90-SB60, iu | 0.035(#3) | 1.61 | 0.38 | 0.56 | 0.5 | 26 |
| 2901-008-0010-02 | VCI-arg90-SB60, iu, Grids<1" | 0.035(#3) | 1.61 | 0.34 | 0.50 | 0.5 | 23 |
| 2901-008-0011-01 | VCI-arg90-VCI-arg90-SB60, iu | 0.035(#5) | 1.55 | 0.36 | 0.51 | 0.5 | 26 |
| 2901-008-0012-01 | SB60-arg90-SB60-arg90-VCI, iu | 0.035(#2, #4) | 1.33 | 0.25 | 0.45 | 0.5 | 24 |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "Shi D", written over a horizontal line.

National Accreditation & Management Institute, Inc.
4794 George Washington Memorial Hwy.
Hayes, VA 23072
Tel.: (804) 684-5124
nami@namiinc.com
namicertification.com