# **NOTICE OF PRODUCT CERTIFICATION**



1	<b>CERTIFICATION NO:</b>
(	DATE:
]	<b>CERTIFICATION PROGRAM:</b>
	COMPANY:
2	CODE:
(	<b>EXPIRATION DATE:</b>

TITICATIONING

NI015750	
03/15/2023	
Fire	
Victory	
2435-1	
03/31/2027	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

PRODUCT DESCRIPTION
<b>Crest Doors Particleboard Core</b>
w/Fiberglass Cladding Fire Door
Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Single Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

## SPECIFICATION

CAN4 S104 (1985)(2010) UL 10C (2001)(2009) NFPA 252 (2008)

#### **PRODUCT RATING**

20 Minute-Positive Pressure With Hose Stream Category B - Additional Edge Sealing System Required

#### **TEST REPORT**

Intertek Test Report No: 3160246MID-005

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com