## **NOTICE OF PRODUCT CERTIFICATION**



<b>CERTIFICATION NO:</b>
DATE:
<b>CERTIFICATION PROGRAM:</b>
<b>COMPANY:</b>
CODE:
<b>EXPIRATION DATE:</b>
EAPIRATION DATE:

NI015751	
03/15/2023	
Fire	
Victory	
2435-1	
03/31/2027	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Victory Doors & Millwork Corporation	<b>Crest Doors 20 Minute Positive Pressure</b>
8685 East Cash Lane	Particleboard Core/Wood Veneer
Nampa, ID 83687	Side-Hinged Door Assembly
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single & Double Swing Only
	Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UBC-7-2-97 UL 10C (1998)(2009) NFPA 252 (1995)(2008)	20 Minute-Positive Pressure w/o Hose Stream Category A Door-No Additional Edge Seal Required Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

## TEST REPORT

Warnock Hershey Test Report No: WHI-495-1367

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com