## **NOTICE OF PRODUCT CERTIFICATION**



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

PRODUCT DESCRIPTION
"HDF/MDF Skin w/Warm Springs Core"
Wood Side Hinged Door
w/X19 Adhesive
Manufacture Specific Fire Doors for Single Swing Installation in 45-Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Maximum Size: 35.81" x 83.5" Minimum Thickness: 1.75"

**SPECIFICATION** 

UL 10(c) (2021)

45 Minute-Positive Pressure With Hose Stream

**PRODUCT RATING** 

Category B- Additional Edge Sealing System Required

## **TEST REPORT**

Intertek Test Report No: 105199609MID-006

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com