NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: DATE: CERTIFICATION PROGRAM: COMPANY: CODE:

| NI015782 |
|-------------|
| 04/13/2023 |
| Structural |
| Linea Rossa |
| 2749-1 |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|---------------------------------------|--|
| Linea Rossa, LLC | Series "GLR-U28" |
| 1850 Northwest 84th Avenue, Suite 114 | Aluminum Sliding Glass Door & |
| Doral, FL 33126 | Lift & Slide System |
| | Configuration: OXXXXO Glazing: IG - 1/4" Heat Strengthened Glass/1/4" Heat Strengthened Glass/0.060" Kuraray PVB Interlayer/1/4" Heat Strengthened Glass or Monolithic - 1/4" Heat Strengthened Glass/0.060" Kuraray PVB Interlayer/1/4" Heat Strengthened Glass or IG - 1/4" Heat Strengthened Glass/1/4" Heat Strengthened Glass or Monolithic - 1/4" Heat Strengthened Glass/0.090" Kuraray PVB Interlayer/1/4" Heat Strengthened Glass or Monolithic - 1/4" Heat Strengthened Glass/0.090" Kuraray PVB Interlayer/1/4" Heat Strengthened Glass/ |
| | Frame: W-8853mm(348.56") H-3048mm(120") |
| | Panel: W-1524mm(60") H-2972mm(117") |
| | DLO: W-1343mm(52.88") H-2794mm(110") |

| SPECIFICATION | PRODUCT RATING |
|--------------------|---|
| TAS 201/202/203-94 | Design Pressure: ±3830 Pa (±80 psf) Large Missile Impact Rated |

Product Tested By: **QAI** Laboratories Report No: 13309 Expiration Date: April 30, 2027

Administrator's Signature:

NATIONAL ACCREDITATION AND **MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com