

# Notice of Product Certification

**CERTIFICATION NO.:** 2932-005  
**INITIAL CERTIFICATION DATE:** June 19, 2023  
**REVISION DATE:** N/A  
**REPORT NUMBER:** FEW23101498-c  
**SPECIFICATION:** CSA A440.2-19

**COMPANY:** Fersina Windows  
**CODE:** 2932-1  
**EXPIRATION DATE:** April 26, 2028  
**PRODUCT SIMULATED BY:** WSP  
**AIR LEAKAGE REPORT NO.:** NCTL-110-19011-2

**PRODUCT/SERIES NAME:** 1800 Aspekt Casement    **OPERATOR TYPE:** CSSV

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-005-0001-01	180-arg97-CCI, ss	0.068(#2)	1.47	0.41	0.50	0.1	31
2932-005-0001-02	180-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.47	0.37	0.45	0.1	29
2932-005-0002-01	272-arg97-CCI, ss	0.042(#2)	1.43	0.26	0.45	0.1	24
2932-005-0002-02	272-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.43	0.24	0.41	0.1	22
2932-005-0003-01	366-arg97-CCI, ss	0.020(#2)	1.40	0.17	0.41	0.1	19
2932-005-0003-02	366-arg97-CCI, ss, Grids<1 Inch	0.020(#2)	1.40	0.16	0.37	0.1	18
2932-005-0004-01	272-arg97-i89, ss	0.042(#2) 0.149(#4)	1.24	0.26	0.44	0.1	28
2932-005-0004-02	272-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#4)	1.24	0.24	0.40	0.1	27
2932-005-0005-01	8071-arg97-CCI, ss	0.082(#2)	1.48	0.42	0.50	0.1	32
2932-005-0005-02	8071-arg97-CCI, ss, Grids<1 Inch	0.082(#2)	1.48	0.38	0.45	0.1	29
2932-005-0006-01	180-arg97-CCI-arg97-CCI, ss	0.068(#2)	1.18	0.38	0.45	0.1	36
2932-005-0006-02	180-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.18	0.34	0.41	0.1	34
2932-005-0007-01	272-arg97-CCI-arg97-CCI, ss	0.042(#2)	1.16	0.24	0.41	0.1	28
2932-005-0007-02	272-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.16	0.22	0.37	0.1	27
2932-005-0008-01	272-arg97-CCI-arg97-272, ss	0.042(#2, #5)	0.94	0.23	0.36	0.1	33
2932-005-0008-02	272-arg97-CCI-arg97-272, ss, Grids<1 Inch	0.042(#2, #5)	0.94	0.21	0.32	0.1	31
2932-005-0009-01	366-arg97-CCI-arg97-180, ss	0.020(#2) 0.068(#5)	0.94	0.16	0.36	0.1	28
2932-005-0009-02	366-arg97-CCI-arg97-180, ss, Grids<1 Inch	0.020(#2) 0.068(#5)	0.94	0.15	0.32	0.1	28
2932-005-0010-01	180-arg97-CCI-arg97-i89, ss	0.068(#2) 0.149(#6)	1.06	0.37	0.44	0.1	38
2932-005-0010-02	180-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.068(#2) 0.149(#6)	1.06	0.33	0.40	0.1	36
2932-005-0011-01	272-arg97-CCI-arg97-i89, ss	0.042(#2) 0.149(#6)	1.04	0.24	0.40	0.1	31
2932-005-0011-02	272-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#6)	1.04	0.22	0.36	0.1	30
2932-005-0012-01	366-arg97-CCI-arg97-i89, ss	0.020(#2) 0.149(#6)	1.03	0.16	0.36	0.1	26
2932-005-0012-02	366-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.020(#2) 0.149(#6)	1.03	0.15	0.33	0.1	26

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-005-0013-01	8071-arg97-CCI-arg97-8071, ss	0.082(#2, #5)	0.98	0.37	0.45	0.1	40
2932-005-0013-02	8071-arg97-CCI-arg97-8071, ss, Grids<1 Inch	0.082(#2, #5)	0.98	0.34	0.40	0.1	38
2932-005-0014-01	180-arg97-CCI, ss, Reinforcement	0.068(#2)	1.51	0.41	0.50	0.1	30
2932-005-0014-02	180-arg97-CCI, ss, Reinforcement, Grids<1 Inch	0.068(#2)	1.51	0.37	0.45	0.1	28

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

National Accreditation & Management Institute, Inc.  
 4794 George Washington Memorial Hwy.  
 Hayes, VA 23072  
 Tel.: (804) 684-5124  
 nami@namiinc.com  
 namicertification.com