

Notice of Product Certification

CERTIFICATION NO.: 2932-007
INITIAL CERTIFICATION DATE: June 19, 2023
REVISION DATE: N/A
REPORT NUMBER: FEW23101498-d
SPECIFICATION: CSA A440.2-19

COMPANY: Fersina Windows
CODE: 2932-1
EXPIRATION DATE: April 26, 2028
PRODUCT SIMULATED BY: WSP
AIR LEAKAGE REPORT NO.: NCTL-110-18114-1

PRODUCT/SERIES NAME: 1800 Aspekt Awning **OPERATOR TYPE:** PRAW

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-007-0001-01	180-arg97-CCI, ss	0.068(#2)	1.47	0.41	0.50	0.3	31
2932-007-0001-02	180-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.47	0.37	0.45	0.3	29
2932-007-0002-01	272-arg97-CCI, ss	0.042(#2)	1.44	0.26	0.45	0.3	23
2932-007-0002-02	272-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.44	0.24	0.41	0.3	22
2932-007-0003-01	366-arg97-CCI, ss	0.020(#2)	1.41	0.17	0.41	0.3	18
2932-007-0003-02	366-arg97-CCI, ss, Grids<1 Inch	0.020(#2)	1.41	0.16	0.37	0.3	18
2932-007-0004-01	272-arg97-i89, ss	0.042(#2) 0.149(#4)	1.27	0.26	0.44	0.3	27
2932-007-0004-02	272-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#4)	1.27	0.24	0.40	0.3	25
2932-007-0005-01	8071-arg97-CCI, ss	0.082(#2)	1.49	0.42	0.50	0.3	31
2932-007-0005-02	8071-arg97-CCI, ss, Grids<1 Inch	0.082(#2)	1.49	0.38	0.45	0.3	29
2932-007-0006-01	180-arg97-CCI-arg97-CCI, ss	0.068(#2)	1.18	0.38	0.45	0.3	36
2932-007-0006-02	180-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.18	0.34	0.41	0.3	33
2932-007-0007-01	272-arg97-CCI-arg97-CCI, ss	0.042(#2)	1.15	0.24	0.41	0.3	28
2932-007-0007-02	272-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.15	0.22	0.37	0.3	27
2932-007-0008-01	272-arg97-CCI-arg97-272, ss	0.042(#2, #5)	0.93	0.23	0.36	0.3	32
2932-007-0008-02	272-arg97-CCI-arg97-272, ss, Grids<1 Inch	0.042(#2, #5)	0.93	0.21	0.32	0.3	31
2932-007-0009-01	366-arg97-CCI-arg97-180, ss	0.020(#2) 0.068(#5)	0.94	0.16	0.36	0.3	28
2932-007-0009-02	366-arg97-CCI-arg97-180, ss, Grids<1 Inch	0.020(#2) 0.068(#5)	0.94	0.14	0.32	0.3	27
2932-007-0010-01	180-arg97-CCI-arg97-i89, ss	0.068(#2) 0.149(#6)	1.07	0.37	0.44	0.3	37
2932-007-0010-02	180-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.068(#2) 0.149(#6)	1.07	0.33	0.40	0.3	35
2932-007-0011-01	272-arg97-CCI-arg97-i89, ss	0.042(#2) 0.149(#6)	1.05	0.24	0.40	0.3	30
2932-007-0011-02	272-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#6)	1.05	0.22	0.36	0.3	29
2932-007-0012-01	366-arg97-CCI-arg97-i89, ss	0.020(#2) 0.149(#6)	1.04	0.16	0.36	0.3	26
2932-007-0012-02	366-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.020(#2) 0.149(#6)	1.04	0.15	0.33	0.3	25

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-007-0013-01	8071-arg97-CCI-arg97-8071, ss	0.082(#2, #5)	0.97	0.37	0.45	0.3	40
2932-007-0013-02	8071-arg97-CCI-arg97-8071, ss, Grids<1 Inch	0.082(#2, #5)	0.97	0.34	0.40	0.3	38
2932-007-0014-01	180-arg97-CCI, ss, Reinforcement	0.068(#2)	1.52	0.41	0.50	0.3	30
2932-007-0014-02	180-arg97-CCI, ss, Reinforcement, Grids<1 Inch	0.068(#2)	1.52	0.37	0.45	0.3	27

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com