

Notice of Product Certification

CERTIFICATION NO.: 2932-008
INITIAL CERTIFICATION DATE: June 19, 2023
REVISION DATE: N/A
REPORT NUMBER: FEW23101498-a
SPECIFICATION: CSA A440.2-19

COMPANY: Fersina Windows
CODE: 2932-1
EXPIRATION DATE: April 25, 2028
PRODUCT SIMULATED BY: WSP
AIR LEAKAGE REPORT NO.: A9014.01-109-47

PRODUCT/SERIES NAME: 4500 Tilt & Turn **OPERATOR TYPE:** DATT

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-008-0001-01	180-arg97-CCI, ss	0.068(#2)	1.51	0.44	0.53	0.1	32
2932-008-0001-02	180-arg97-CCI, ss, Grids<1"	0.068(#2)	1.51	0.39	0.47	0.1	29
2932-008-0002-01	272-arg97-CCI, ss	0.042(#2)	1.47	0.28	0.48	0.1	24
2932-008-0002-02	272-arg97-CCI, ss, Grids<1"	0.042(#2)	1.47	0.25	0.42	0.1	22
2932-008-0003-01	366-arg97-CCI, ss	0.020(#2)	1.44	0.19	0.43	0.1	19
2932-008-0003-02	366-arg97-CCI, ss, Grids<1"	0.020(#2)	1.44	0.17	0.38	0.1	18
2932-008-0004-01	272-arg97-i89, ss	0.042(#2) 0.149(#4)	1.28	0.28	0.47	0.1	28
2932-008-0004-02	272-arg97-i89, ss, Grids<1"	0.042(#2) 0.149(#4)	1.28	0.25	0.41	0.1	26
2932-008-0005-01	8071-arg97-CCI, ss	0.082(#2)	1.53	0.45	0.54	0.1	32
2932-008-0005-02	8071-arg97-CCI, ss, Grids<1"	0.082(#2)	1.53	0.40	0.47	0.1	29
2932-008-0006-01	180-arg97-CCI-arg97-CCI, ss	0.068(#2)	1.23	0.40	0.48	0.1	36
2932-008-0006-02	180-arg97-CCI-arg97-CCI, ss, Grids<1"	0.068(#2)	1.23	0.36	0.43	0.1	34
2932-008-0007-01	272-arg97-CCI-arg97-CCI, ss	0.042(#2)	1.21	0.26	0.44	0.1	28
2932-008-0007-02	272-arg97-CCI-arg97-CCI, ss, Grids<1"	0.042(#2)	1.21	0.23	0.39	0.1	27
2932-008-0008-01	272-arg97-CCI-arg97-272, ss	0.042(#2, #5)	0.98	0.24	0.38	0.1	32
2932-008-0008-02	272-arg97-CCI-arg97-272, ss, Grids<1"	0.042(#2, #5)	0.98	0.21	0.34	0.1	30
2932-008-0009-01	366-arg97-CCI-arg97-180, ss	0.020(#2) 0.068(#5)	0.98	0.17	0.38	0.1	28
2932-008-0009-02	366-arg97-CCI-arg97-180, ss, Grids<1"	0.020(#2) 0.068(#5)	0.98	0.15	0.34	0.1	27
2932-008-0010-01	180-arg97-CCI-arg97-i89, ss	0.068(#2) 0.149(#6)	1.11	0.39	0.47	0.1	38
2932-008-0010-02	180-arg97-CCI-arg97-i89, ss, Grids<1"	0.068(#2) 0.149(#6)	1.11	0.35	0.42	0.1	36
2932-008-0011-01	272-arg97-CCI-arg97-i89, ss	0.042(#2) 0.149(#6)	1.09	0.25	0.43	0.1	30
2932-008-0011-02	272-arg97-CCI-arg97-i89, ss, Grids<1"	0.042(#2) 0.149(#6)	1.09	0.23	0.38	0.1	29
2932-008-0012-01	366-arg97-CCI-arg97-i89, ss	0.020(#2) 0.149(#6)	1.08	0.17	0.39	0.1	26
2932-008-0012-02	366-arg97-CCI-arg97-i89, ss, Grids<1"	0.020(#2) 0.149(#6)	1.08	0.15	0.34	0.1	25

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-008-0013-01	8071-arg97-CCI-arg97-8071, ss	0.082(#2, #5)	1.02	0.39	0.48	0.1	40
2932-008-0013-02	8071-arg97-CCI-arg97-8071, ss, Grids<1"	0.082(#2, #5)	1.02	0.35	0.42	0.1	38
2932-008-0014-01	180-arg97-CCI, ss, Reinforcement	0.068(#2)	1.64	0.44	0.53	0.1	29
2932-008-0014-02	180-arg97-CCI, ss, Reinforcement, Grids<1"	0.068(#2)	1.64	0.39	0.47	0.1	26

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "Shirley".

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com