

# Notice of Product Certification

**CERTIFICATION NO.:** 2932-009  
**INITIAL CERTIFICATION DATE:** June 19, 2023  
**REVISION DATE:** N/A  
**REPORT NUMBER:** FEW23101498-b  
**SPECIFICATION:** CSA A440.2-19

**COMPANY:** Fersina Windows  
**CODE:** 2932-1  
**EXPIRATION DATE:** April 25, 2028  
**PRODUCT SIMULATED BY:** WSP  
**AIR LEAKAGE REPORT NO.:** B8186.01-109-47

**PRODUCT/SERIES NAME:** 4500 Fixed    **OPERATOR TYPE:** FIXD

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-009-0001-01	180-arg97-CCI, ss	0.068(#2)	1.50	0.52	0.64	0.2	37
2932-009-0001-02	180-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.50	0.47	0.57	0.2	34
2932-009-0002-01	272-arg97-CCI, ss	0.042(#2)	1.45	0.33	0.58	0.2	27
2932-009-0002-02	272-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.45	0.30	0.52	0.2	25
2932-009-0003-01	366-arg97-CCI, ss	0.020(#2)	1.41	0.22	0.52	0.2	21
2932-009-0003-02	366-arg97-CCI, ss, Grids<1 Inch	0.020(#2)	1.41	0.20	0.46	0.2	20
2932-009-0004-01	272-arg97-i89, ss	0.042(#2) 0.149(#4)	1.22	0.33	0.56	0.2	32
2932-009-0004-02	272-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#4)	1.22	0.30	0.50	0.2	30
2932-009-0005-01	8071-arg97-CCI, ss	0.082(#2)	1.52	0.54	0.64	0.2	38
2932-009-0005-02	8071-arg97-CCI, ss, Grids<1 Inch	0.082(#2)	1.52	0.48	0.57	0.2	34
2932-009-0006-01	180-arg97-CCI-arg97-CCI, ss	0.068(#2)	1.17	0.48	0.58	0.2	42
2932-009-0006-02	180-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.068(#2)	1.17	0.43	0.52	0.2	39
2932-009-0007-01	272-arg97-CCI-arg97-CCI, ss	0.042(#2)	1.15	0.31	0.53	0.2	32
2932-009-0007-02	272-arg97-CCI-arg97-CCI, ss, Grids<1 Inch	0.042(#2)	1.15	0.28	0.47	0.2	31
2932-009-0008-01	272-arg97-CCI-arg97-272, ss	0.042(#2, #5)	0.87	0.28	0.46	0.2	37
2932-009-0008-02	272-arg97-CCI-arg97-272, ss, Grids<1 Inch	0.042(#2, #5)	0.87	0.26	0.41	0.2	36
2932-009-0009-01	366-arg97-CCI-arg97-180, ss	0.020(#2) 0.068(#5)	0.87	0.20	0.46	0.2	32
2932-009-0009-02	366-arg97-CCI-arg97-180, ss, Grids<1 Inch	0.020(#2) 0.068(#5)	0.87	0.18	0.41	0.2	31
2932-009-0010-01	180-arg97-CCI-arg97-i89, ss	0.068(#2) 0.149(#6)	1.02	0.46	0.57	0.2	44
2932-009-0010-02	180-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.068(#2) 0.149(#6)	1.02	0.42	0.51	0.2	42
2932-009-0011-01	272-arg97-CCI-arg97-i89, ss	0.042(#2) 0.149(#6)	1.00	0.30	0.51	0.2	35
2932-009-0011-02	272-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.042(#2) 0.149(#6)	1.00	0.27	0.46	0.2	33
2932-009-0012-01	366-arg97-CCI-arg97-i89, ss	0.020(#2) 0.149(#6)	0.98	0.20	0.46	0.2	30
2932-009-0012-02	366-arg97-CCI-arg97-i89, ss, Grids<1 Inch	0.020(#2) 0.149(#6)	0.98	0.18	0.41	0.2	29

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2932-009-0013-01	8071-arg97-CCI-arg97-8071, ss	0.082(#2, #5)	0.92	0.47	0.57	0.2	47
2932-009-0013-02	8071-arg97-CCI-arg97-8071, ss, Grids<1 Inch	0.082(#2, #5)	0.92	0.42	0.51	0.2	44
2932-009-0014-01	180-arg97-CCI, ss, Reinforcement	0.068(#2)	1.59	0.52	0.64	0.2	35
2932-009-0014-02	180-arg97-CCI, ss, Reinforcement, Grids<1 Inch	0.068(#2)	1.59	0.47	0.57	0.2	32

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

National Accreditation & Management Institute, Inc.  
 4794 George Washington Memorial Hwy.  
 Hayes, VA 23072  
 Tel.: (804) 684-5124  
 nami@namiinc.com  
 namicertification.com