

# NOTICE OF PRODUCT CERTIFICATION



**Company:** BMC Millwork  
105 Broughton Street  
Ailey, GA 30410

**Certification No.:** NI014388-R1  
**Certification Date:** 04/16/2019  
**Expiration Date:** 04/30/2026  
**Revision Date:** 07/20/2023

**Product:** Metal-Edge Steel Opaque Inswing or Outswing Door w/ & w/o Impact Rated Sidelites  
(w/Wood Frame unless noted)

**Specification:** TAS 201/202/203-94

**Glazing:** Insulating Glass: 1/8" Tempered Glass/1/8" Heat Strengthened Glass/0.090" Saflex PVB  
Interlayer/1/8" Heat Strengthened Glass

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+40/-45	0.0 psf	Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
X Single	O/S	Glazed	3'0" x 6'8"	+45/-40	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 7.50 psf <sup>3,4,5</sup>	Yes	ATLNC 0124.01-17/W-1857/W-1885 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XX Double	I/S	Glazed	3'0" x 6'8"	+40/-45	0 psf	Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XX Double	O/S	Glazed	3'0" x 6'8"	+45/-40	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XO/OX Single w/Sidelite	O/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+45/-40	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelite	9'0" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelite	9'0" x 6'8"	+45/-40	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXXO Double w/Sidelites	I/S	Glazed Door Glazed Sidelite	12'4" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXXO Double w/Sidelites	O/S	Glazed Door Glazed Sidelite	12'4" x 6'8"	+45/-40	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-Yes Sidelite-Yes	ATLNC 0124.01-17/W-1885 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Pro T4 Threshold 5-HP Outswing Threshold

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072**  
**Tel: (804) 684-5124/Fax: (804) 684-5122**

**NAMI AUTHORIZED SIGNATURE:** \_\_\_\_\_