## **NOTICE OF PRODUCT CERTIFICATION**



CERTIFICATION NO: DATE: CERTIFICATION PROGRAM: COMPANY: CODE:

NI015830.01	
07/20/2023	
Structural	
Ply Gem	
1408-1	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
Ply Gem Window Group	Series "4700/4701 FLIR & 4701 FIR"	
433 North Main Street	Aluminum Fixed Lite	
Rocky Mount, VA 24151	Configuration: O Glazing: IG-1/8" Annealed Glass/1/8" Annealed Glass/0.090" Eastman PVB Interlayer/1/8" Annealed Glass	
	Frame: W-1348mm(53.06") H-1880mm(74")	
	DLO: W-1253mm(49.31") H-1788mm(70.38")	

SPECIFICATION	PRODUCT RATING
AAMA 506-06/08/11/16 AAMA/WDMA/CSA 101/I.S.2/A440-11 AAMA/WDMA/CSA 101/I.S.2/A440-08 AAMA/WDMA/CSA 101/I.S.2/A440-05	Class LC-PG60 1348 x 1880* (53 x 74*)-FW FW LC-PG 1348 x 1880* (53 x 74*) Design Pressure: ±2873 Pa (±60 psf) Positive Design Pressure: 3840 Pa (80 psf) Negative Design Pressure: 3840 Pa (80 psf) Water Penetration Resistance Test Pressure: 440 Pa (9.19 psf) <u>ASTM Impact Rating</u> Design Pressure: ±2349 Pa (±50 psf) Positive Design Pressure: 2349 Pa (50 psf) Negative Design Pressure: 2729 Pa (57 psf) Wind Zone 3 - Missile Level D

Product Tested By: Report No: Expiration Date:

Administrator's Signature:-

National Certified Testing Laboratories 110-26154-1/110-13668-1/110-25962-1 July 31, 2027

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com